



**Medium**

## CERES S3

**Low-cut safety shoe in nubuck, designed for ladies**

The Safety Jogger CERES is a low-cut safety shoe made of nubuck, offering top-notch protection and comfort. It features an SR slip-resistant rubber outsole, composite toecap, and SJ Flex material, making it lightweight and perfect for various industries.

|               |  |
|---------------|--|
| Upper         | Nubuck Action Leather  |
| Lining        | 3D-Mesh  |
| Footbed       | SJ foam footbed  |
| Midsole       | Anti-puncture Textile  |
| Outsole       | Rubber (NBR)   |
| Toecap        | Composite  |
| Category      | S3 / SRC, HRO  |
| Size range    | EU 36-42 / UK 3.5-8.0 / US 6.0-10.5<br>JPN 22.5-26.5 / KOR 235-270 |
| Sample weight | 0.470 kg   |
| Norms         | ASTM F2413:2018<br>EN ISO 20345:2011                               |



210



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

**Metal free**  
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

**Composite toecap**  
Metalfree and lightweight, no thermal or electrical conductivity

**SJ Flex**  
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

**Water resistant Upper (WRU)**  
Prevents penetration of water if not permanently exposed to high levels.

**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Industries:**

Automotive, Catering, Chemical, Cleaning, Construction, Food &amp; beverages, Mining, Logistics, Oil &amp; Gas, Industry

**Environments:**

Dry environment, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

|                | Description  | Measure unit          | Result      | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| <b>Upper</b>   | <b>Nubuck Action Leather</b>                                     |                       |             |              |
|                | Upper: permeability to water vapor                               | mg/cm <sup>2</sup> /h | 3.3         | ≥ 0.8        |
|                | Upper: water vapor coefficient                                   | mg/cm <sup>2</sup>    | 27.3        | ≥ 15         |
| <b>Lining</b>  | <b>3D-Mesh</b>   |                       |             |              |
|                | Lining: permeability to water vapor                              | mg/cm <sup>2</sup> /h | 86.9        | ≥ 2          |
|                | Lining: water vapor coefficient                                  | mg/cm <sup>2</sup>    | 695.4       | ≥ 20         |
| <b>Footbed</b> | <b>SJ foam footbed</b>   |                       |             |              |
|                | Footbed: abrasion resistance (dry/wet) (cycles)                  | cycles                | 25600/12800 | 25600/12800  |
| <b>Outsole</b> | <b>Rubber (NBR)</b>  |                       |             |              |
|                | Outsole abrasion resistance (volume loss)                        | mm <sup>3</sup>       | 82.6        | ≤ 150        |
|                | Outsole slip resistance SRA: heel                                | friction              | 0.34        | ≥ 0.28       |
|                | Outsole slip resistance SRA: flat                                | friction              | 0.36        | ≥ 0.32       |
|                | Outsole slip resistance SRB: heel                                | friction              | 0.14        | ≥ 0.13       |
|                | Outsole slip resistance SRB: flat                                | friction              | 0.22        | ≥ 0.18       |
|                | Antistatic value   | MegaOhm               | 24.5        | 0.1 - 1000   |
|                | ESD value  | MegaOhm               | N/A         | 0.1 - 100    |
|                | Heel energy absorption   | J                     | 24          | ≥ 20         |
| <b>Toecap</b>  | <b>Composite</b>   |                       |             |              |
|                | Impact resistance toecap (clearance after impact 100J)           | mm                    | N/A         | N/A          |
|                | Compression resistance toecap (clearance after compression 10kN) | mm                    | N/A         | N/A          |
|                | Impact resistance toecap (clearance after impact 200J)           | mm                    | 18.0        | ≥ 14         |
|                | Compression resistance toecap (clearance after compression 15kN) | mm                    | 19.0        | ≥ 14         |

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.