



# SAFETY JOGGER

## PROFESSIONAL



Light

## HENNY OB

**Sporty and fashionable sneaker for him**

The HENNY shoes provide superior support, excellent grip and moisture-wicking properties. Ideal for those working in the cleaning, food & beverages, and medical industries.

Upper	Synthetic Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	TPR
Category	OB / E
Size range	EU 39-47 / UK 6.0-12.0 / US 6.5-13.0 JPN 25-31 / KOR 255-310
Sample weight	0.390 kg
Norms	EN ISO 20347:2022(Europe)



LGR



NAV



**Coolmax® lining**  
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



### Solutions for every workplace

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

**Industries:**

Cleaning, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	16.8	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	51	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	408.7	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>TPR</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	145	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.35	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.39	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
ESD value	MegaOhm	N/A	0.1 - 100	
	Heel energy absorption	J	24	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.