



Heavy

OXYVA OB

Superior clog with unmatched comfort

The lightweight OXYVA clogs offer safety and hygiene with their ESD feature, waterproof and antibacterial material, and are washable at 30°C. Suitable for various industries, they provide superior body support while being cost-effective.

| | |
|---------------|---|
| Upper | Expanded EVA |
| Lining | N/A |
| Footbed | Comfort Footbed |
| Outsole | Expanded EVA |
| Category | OB / SR, ESD, A, E |
| Size range | EU 35-46 / UK 3.0-11.0 / US 3.0-12.0 JPN 21.5-30 / KOR 230-300 |
| Sample weight | 0.175 kg |
| Norms | ASTM F2892:2018 EN ISO 20347:2022(Europe) |



EBL



BLK



EGN



FUX



LIC



NAV



WHT



Hygienic waterproof solution

This shoe is made with materials that are waterproof, antibacterial and extremely light & flexible. This makes it a safe, hygienic and comfortable solution for applications in wet environments, such as cleaning or escorting patients into the shower.




Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Washable 30°C

These shoes can be washed in a washing machine at 30°C.



Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.

Industries:

Medical, Catering, Cleaning, Food & beverages

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Expanded EVA | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | N/A | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | N/A | ≥ 15 |
| Lining | N/A | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | N/A | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | N/A | ≥ 20 |
| Footbed | Comfort Footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | Expanded EVA | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 130 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.31 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.36 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.19 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.22 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 29.4 | 0.1 - 1000 |
| | ESD value | MegaOhm | 6.8 | 0.1 - 100 |
| | Heel energy absorption | J | 77 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.